

Technical Data Sheet

EKOSIGNOL THINNER



product description:	EKOSIGNOL THINNER is a mixture of organic solvents.
intended use:	It is used for diluting EKOSIGNOL PAINT for thin-layer horizontal road marking and washing tools. EKOSIGNOL THINNER is compatible with all shades of EKOSIGNOL PAINT for thin-layer horizontal road marking as well as with all types of glass beads intended for horizontal signalization.
assortment:	EKOSIGNOL THINNER
appearance:	Clear, colourless to slightly yellowish liquid
density:	0.84 kg/l (EN ISO 2811-1)
volatile organic compounds content (VOC):	840 g/l (EN ISO 11890-1)
working conditions:	The air temperature, the temperature of material and surface during processing must be higher than +10 °C, less than +25 °C, and relative humidity less than 75 %.
safety measures:	Keep away from heat and sources of ignition. Use non-sparking tools. Prevent leakage and spillage into watercourses and drainage systems. Avoid heat, sparks, static electricity and flames and contact with strong oxidants. Keep out of the reach of children. Wear protective equipment. Read the safety data sheet of the product before use.
transport and storage:	In accordance with the regulations on storage of flammable liquids.
shelf life:	In unopened packaging unlimited from the date of manufacture.
product/packaging disposal:	Empty the packaging completely. Dispose of in accordance with valid regulations to an authorized waste collector.
quality control:	Product quality characteristics are determined by internal production specifications and European and Croatian standards. The product is under the constant supervision of factory quality control Chromos-Svjetlost d.o.o.
disclaimers:	<p>Before using the product, please check its quality. In case of any major deviations from the declared properties of the product, stop the use and contact the manufacturer; otherwise any subsequent complaints will not be accepted.</p> <p>Technical data are the result of our technical and experimental knowledge, and are provided with the intention of achieving optimal results in working with CHROMOS- SVJETLOST products. The data does not contain a legal or secondary obligation of the manufacturer nor does it release the user from the obligation to check the suitability of the product for particular purpose. Due to the use of natural raw materials in our products, minor deviations from certain values are possible for individual deliveries. Contact our Technical service before use on substrates not listed in the accompanying documentation. The manufacturer reserves the right to make any subsequent changes to the Technical Data Sheet. Only the latest edition is valid. Updated Technical Data Sheets can be found on the website www.chromos-svjetlost.hr or can be requested from the manufacturer via the contact e-mail address below. Contact our Technical service for more detailed information. Be sure to read the safety labels on the product packaging before use. Safety Data Sheet is available on request.</p>

October, 2021.

Quality and Environmental management systems certified in accordance with TÜV NORD Croatia;
Certificate No: 44 100 134668 / 44 104 134668

