

Tehničke informacije

TOP PREMIUM

High-quality paint for interior walls with great coverage



product description: High-quality dispersion paint for interior walls with great opacity. Creates a firm, resistant and washable film. It is possible to wipe off impurities that are not greatly adhered with a soft cloth dipped in universal cleaning solution. Intended for the decoration and protection of interior walls, and for quickly renewing paint on wall and ceiling surfaces. Easy to apply, in certain cases one layer of paint is enough due to high coverage.

area of plication: Used for surfaces made of underlying lime-cement plasters, concrete, levelling compounds, gyps-cardboard and fibre-cement panels, plywood plasters, structured wallpaper, as well as for surfaces with solid old coatings that require renewal.

product range: It is produced in 12 standard shades.



dilution: Dilution is not required or in exceptional circumstances, up to 5%.

coverage: 7-8 m²/l, for 1 layer, depending on the roughness and absorbency of the substrate.

non-volatile-matter content: 55- 65 % (EN ISO 3251).

density: 1,45-1,60 kg/l (EN ISO 2811-1).

volatile organic compounds content: A(a), 30 g/l; max. 5 g/l (EN ISO 11890-1).

technical data according to EN 13300

Largest grain size (EN 21524)	Fine < 100 µm
Wet scrub resistance (EN ISO 11998)	Class 2
Opacity (EN ISO 6504-3)	Class 1 with declared coverage
Gloss (EN ISO 2813)	Matt

Tehničke informacije

TOP PREMIUM

High-quality paint for interior walls with great coverage



working conditions:	The temperature of the air, material and surface during processing must be higher than +5 °C and lower than +30 °C, and the relative humidity lower than 80 %. Low temperatures as well as high air humidity prolong the drying time and can change the shade unevenly. High temperature in summer shortens the open working time of the material.
preparation of the substrate:	The substrate must be completely dry, smooth, clean, free of loose parts, dust, grease stains, mould and other foreign bodies. Before each painting, the substrate must be inspected and its condition determined. All loose parts of the substrate and old coatings should be removed. The resulting unevenness, depending on their depth, should be filled with appropriate restoration plaster or evened out using levelling compounds. New lime and cement plasters must dry for at least 14 days, levelling compounds for a minimum of one day per millimetre of thickness, and new concrete substrates for a minimum of one month. Substrates contaminated by mould should be treated with <i>Algenon</i> or <i>Algenon Plus</i> biocidal solution, then cleaned with a cloth or brush and a universal cleaning solution. The best solution against formation and development of mould is to remove their source (regular ventilation, isolation of cold bridges, removing humidity sources, waterproofing...). Greasy and heavily soiled areas should be cleaned with a <i>Kalijev sapun</i> solution. Glossy and water-washable coatings must be roughened with sandpaper beforehand. Coat the new substrates with <i>Simpra universal primer</i> impregnation. Top Premium must be applied on a completely dry surface, at least 6 hours after the application of the primer, depending on weather conditions.
material preparation and application:	<p>No special preparation of the paint is need - if a thin liquid has separated on the surface during transport or long-term storage, the material should be mixed well in the original packaging before use. The product can be used even if further diluted, but certain product characteristics can no longer be achieved (degree of gloss, coverage, degree of whiteness, resistance to wet washing, etc.) TOP PREMIUM is applied using a painter's brush, short-bristle fur or textile paint roller (bristle length of 10-12 mm) in one or two layers. When using a roller, use a suitable paint roller net. A second coat is applied only when the previous one is completely dry (approx. 4-6 h). Apply products from the same production batch to the same surface. Different production batches must be cross mixed before use.</p> <p>When using the product, prepare a sufficient amount of the product to treat one surface, keeping the rest sealed in the original packaging. Do not store already diluted product! In order to avoid visible points of connection and traces of the roller or brush, we recommend applying the paint film "wet on wet", without interruption from one end of the surface to the other. Subsequent repairs are not allowed. We recommend that the paint first be applied along the edges of the walls with a brush, and then with a roller while evening out the points of connection. Additional paint correction during the application is not allowed (dilution, addition of colorants, etc.).</p> <p>Wash the tools with water immediately after working.</p> <p>Adhere to the applicable construction standards when applying the products.</p> <p>If you have any concerns, please contact your Chromos-Svjetlost sales-technical advisor.</p>
drying of the coating:	<p>Recoat interval 4-6 h (20 °C and 65% relative humidity).</p> <p>Completely dry: 6- 12 hours (20 °C and 65% relative humidity).</p> <p>Depending on weather conditions, the specified period can be longer or shorter.</p>
maintenance of interior walls:	Dust the surfaces, clean the stains with a soft cloth. Surfaces from which it is not possible to remove dirt or stains should be repainted (new application of paint in two layers, see preparation of the material).

Tehničke informacije

TOP PREMIUM

High-quality paint for interior walls with great coverage



safety measures:	It is necessary to follow the general rules for construction works. Keep out of reach of children. Wear protective equipment. Before use, read the Technical and Safety Data Sheet of the product.
transport and storage:	Store in a dry and well-ventilated place out of direct sunlight at a temperature of +5 to +25 ° C. Do not expose the product to direct sunlight and protect it from freezing.
shelf life:	1,5 years in unopened packaging.
disposal of leftover product and packaging:	Empty the packaging of its contents completely. Dispose of it at a recycling yard. Legal entities must deliver the packaging as packaging waste to a licensed waste
quality control:	Product quality characteristics are determined by internal production specifications as well as European and Croatian standards. The product is under constant supervision of the factory quality control of Chromos-Svjetlost d.o.o.
general remarks:	<p>Before use, the customer must check the quality of the product, and upon noticing any incompatibility must stop the application and contact the manufacturer, otherwise a complaint will not be accepted.</p> <p>Mechanical damage on dark colours causes the appearance of light stripes. This phenomenon is specific to dark colours and does not affect the quality of the coating.</p> <p>Technical data are the result of our technical and experimental knowledge, and are provided with an intention of achieving optimal results in working with CHROMOS-SVJETLOST products. The date does not contain a legal or secondary obligation of the manufacturer or release the user from the obligation to check the suitability of the product for particular purpose. Due to the use of natural raw materials in our products, minor deviations from certain values are possible for individual deliveries. When is to be used on substrates which are not listed in the accompanying documentation, the manufacturer must be consulted. The manufacturer reserves the right to make any subsequent changes to the technical data sheet. Only the latest edition is valid. Updated technical data sheets can be found on the website www.chromos-svjetlost.hr or can be requested from the manufacturer via the contact e-mail address below. Contact our technical service for more detailed information. Be sure to read the safety labels on the product packaging before use, while the Safety Data Sheets are available on request.</p>

February, 2024

Quality and environmental protection management system certified by TUV Croatia;
Certificate numbers: 44 100 134668 / 44 104 134668