

## Technical data sheet

# ULTRA WOOD FILLER

One-component quick-drying wood filler kit



<b>product description:</b>	ULTRA wood kit is a one-component quick-drying dispersion mass for quality filling and correcting minor irregularities and surface damage cracks, dents and gaps on wood surfaces.
<b>area of application:</b>	It is used for filling and correcting minor irregularities and surface damages on wood surfaces.
<b>product range:</b>	ULTRA WOOD KIT in shades: white, pine, beech, oak, mahogany and spruce. Kits in different shades may be mixed in arbitrary proportions.
<b>coverage:</b>	1 m <sup>2</sup> /l in one layer
<b>density:</b>	1.7 kg/l (depending on the shade) (HRN EN ISO 2811-1:2016)
<b>non-volatile compounds content:</b>	77 % (in weight); 56% (in volume) - depending on the shade (HRN EN ISO 3251:2019)
<b>work conditions:</b>	Air, material and substrate temperature must be higher than +10 °C and lower than +25 °C, while the relative air humidity must be lower than 75 %.
<b>material application:</b>	<p>The substrate must be firm, dry, without loosely attached parts, dust, grease and other impurities. The humidity of the wood must not exceed 12%. Clean resinous surfaces with nitro thinner and dry. We apply it to the thus cleaned and dry surface with a stainless spatula so as to fill all cracks, scratches or other damages. In deeper cracks and holes, the kit is applied in several layers, so that the thickness of each layer is no more than 2 to 3 mm, and each subsequent layer is applied on top of the completely dry previous layer. Sand the dry surface by hand or by machine with fine sandpaper. All types of coatings may be applied on thusly treated surface. Dilute with water if necessary.</p> <p>In case of any questions, contact the sales and technical advisor of Chromos-Svjetlost.</p>
<b>drying of the coating:</b>	<p>- To the touch (for manipulation): 20 min</p> <p>- Completely: 4 hours</p>
<b>transport and storage:</b>	Store in dry and aired areas away from direct sunlight at temperatures ranging from +5 +25 °C. Do not expose the product to direct sunlight, in winter protect from freezing.
<b>shelf life:</b>	18 months in unopened packaging
<b>remarks:</b>	Keep the product from freezing!
<b>certificates:</b>	For each batch of the product, corresponding certificate is being issued.
<b>disposal of leftover product and packaging:</b>	Empty the packaging of its contents completely. Dispose of it at a recycling yard. Legal persons must deliver the packaging as packaging waste to a licenced waste collector.
<b>quality control:</b>	Product quality characteristics are determined by internal production specifications as well as European and Croatian standards The product is under constant supervision of the factory quality control of Chromos-Svjetlost d.o.o.
<b>general remarks:</b>	The technical data are the result of our technical knowledge and experience, and are provided with the intention of achieving optimal results when working with CHROMOS- SVJETLOST products. The data do not contain any legal or secondary obligation on the part of the manufacturer nor do they release the customer from the obligation to verify the suitability of the product for a specific purpose. Due to the use of natural raw materials in our products, minor deviations minor deviations from certain values are possible during individual deliveries. For changes

Technical data sheet

# ULTRA WOOD FILLER

*One-component quick-drying wood filler kit*



	<p>on substrates that are not specified in corresponding documentation, consult the manufacturer. The manufacturer reserves the right to make further changes to the technical data sheet. Only the latest version is valid. Updated technical data sheets are available at <a href="http://www.chromos-svjetlost.hr">www.chromos-svjetlost.hr</a> or can be requested from the manufacturer via the contact e-mail listed below. For more detailed information, please contact our technical service. Before use, read the safety labels on the product packaging, while the Technical and Safety Sheets are available on request.</p>
<p>October, 2021</p>	<p>Quality and environmental protection management system certified by TUV Croatia; Certificate numbers: 44 100 134668 / 44 104 134668</p> 

