

Technical Data Sheet

AQUALUX SHABBY CHIC

Water-based decorative wood coating



product description:	AQUALUX SHABBY CHIC is a chalky paint based on acrylic polymer for decorating wooden surfaces and furniture in the "Shabby Chic" look.
area of application:	Decorative coating for wooden surfaces and furniture.
product range:	Shabby Chic Shades: White Lace, Mystery Gray, Royal Champagne, Powder Pink, Malachite Green, Turquoise Star
properties:	The product is: Ecologically acceptable Non-toxic Non-flammable
thinner:	Dilution is not required.
coating appearance:	Matt
coverage:	8 – 10 m ² /l of surface in 1 layer, depending on the method of application and the thickness of the coating.
consumption:	0.10 l/m ² in one layer
density:	1.40 – 1.50 kg/l, (EN ISO 2811-1)
supplying viscosity:	2000 – 5000 mPa·s (20 °C) (EN ISO 2555), depending on the shade.
non-volatile-matter content:	50 – 52 % by weight, 40 – 42 % by volume (EN ISO 3251)
volatile organic compound (VOC) content:	A(d) 130 g/l; max. 10 g/l (EN ISO 11890-1)
working conditions:	The temperature of the air, material and substrate during processing must be higher than +10 °C, less than +25 °C, and relative humidity less than 75 %.
material preparation:	Stir well before using AQUALUX SHABBY CHIC! The surface should be dry and clean, pre-sanded and dusted.
application:	Apply the coating in different directions and thicknesses, depending on the desired final appearance, in one coat. Leave to dry for 1 hour, then gently sand the desired parts with fine sandpaper to make the substrate visible. Immediately after use, close the packaging well and wash the tool with water! For any additional info, please contact a Chromos-Svjetlost technical advisor.
decoration suggestion:	Choose two different Aqualux Shabby Chic shades. Apply the first shade over the entire surface as a base that will be visible later. When it dries, apply a different, contrasting shade in different directions and coats. The interval between coats is 1 h. When the coating is dry, sand the desired parts of the surfaces (edges, prominent parts of the furniture) and then protect the surface with AQUALUX stain or AQUALUX varnish.
drying time:	Touch dry: 30 min / 20 °C, with 65% relative humidity; Completely dry: 1 h.
overcoating interval:	1 h / 20 °C, with 65% relative humidity.
storage conditions:	Store in a dry and well-ventilated place out of direct sunlight at a temperature between +5 °C and 25 °C.

Technical Data Sheet

AQUALUX SHABBY CHIC

Water-based decorative wood coating



product/packaging disposal:	Empty the packaging completely. Dispose of in accordance with valid regulations to an authorized waste collector.
shelf life:	In closed packaging 24 months from the date of manufacture.
notes:	The product is not flammable! KEEP FROM FREEZING! Shake the product well before use!
certificates:	For each production batch, the relevant documentation is submitted.
quality control:	Product quality characteristics are determined by internal production specifications, as well as European and Croatian standards. The product is under the constant supervision of factory quality control Chromos-Svjetlost d.o.o.
disclaimers:	<p>Technical values refer to basic products. Tinting the product may cause minor deviations in certain technical characteristics. Depending on the properties of the substrate and the method of application of the product, minor deviations in shade in relation to the tone chart are possible. The product shade should be checked on a small test surface before use, as we will not be able to accept any subsequent complaints.</p> <p>Before using the product, please check its quality. In case of any major deviations from the declared properties of the product, stop the use and contact the manufacturer; otherwise any subsequent complaints will not be accepted.</p> <p>Technical data are the result of our technical and experimental knowledge, and are provided with the intention of achieving optimal results in working with CHROMOS-SVJETLOST products. The data does not contain a legal or secondary obligation of the manufacturer nor does it release the user from the obligation to check the suitability of the product for particular purpose. Due to the use of natural raw materials in our products, minor deviations from certain values are possible for individual deliveries. Contact our Technical service before use on substrates not listed in the accompanying documentation. The manufacturer reserves the right to make any subsequent changes to the Technical Data Sheet. Only the latest edition is valid. Updated Technical Data Sheets can be found on the website www.chromos-svjetlost.hr or can be requested from the manufacturer via the contact e-mail address below. Contact our Technical service for more detailed information. Be sure to read the safety labels on the product packaging before use. Safety Data Sheet is available on request.</p>

October, 2021.

Quality and Environmental management systems certified in accordance with TÜV NORD Croatia;
Certificate No: 44 100 134668 / 44 104 134668

