

Technical Data Sheet

MAESTRO PROFI PUTTYING LIQUID

fast-drying liquid for filling joints of parquet



product description:	Fast-drying liquid based on modified binders in organic solvents. The liquid is characterized by high elasticity, excellent ability to fill cracks, joints and minor damage to wooden or parquet floors, as well as the property that it does not change the shade of sawdust when drying the filled joint.
field of application:	It is used to fill joints, minor damages and unevenness in the parquet surface treatment system.
assortment:	MAESTRO PROFI PUTTYING LIQUID
thinner:	Maestro profi puttying liquid is not diluted. To wash tools, use Maestro equipment cleaner.
coverage:	8 – 15 m ² /l depending on the size of the joints
consumption:	0.06 – 0.125 l / m ² depending on the size of the joints
density:	0.93 – 0.95 kg/l (EN ISO 2811-1)
viscosity:	1500 – 12500 mPa·s (EN ISO 2555, V3, 50 rpm, 20 °C)
non-volatile-matter content:	14 % (EN ISO 3251)
working conditions:	The temperature of the air, material and substrate during processing must be higher than +10 °C, less than +25 °C, and relative humidity less than 75 %.
previous coatings:	MAESTRO impregnation
application:	The liquid must be stirred before use. On previously sanded parquet with sandpaper no. 60 – 80, a liquid to which wood dust has been added is applied. The liquid is applied with a trowel in 1-2 layers depending on the size of the joints. To fill the joints, you should use wood dust from the parquet being processed so that the shade of the filled surface does not deviate from the shade of the parquet. The dried liquid layer must be well sanded with sandpaper no. 80-100. For any additional info, please contact a Chromos-Svjetlost technical advisor.
drying time:	Up to 60 minutes under normal conditions (working temperature 18-22 °C, relative air humidity up to 65 %, parquet humidity between 8 and 10 %)
overcoating interval:	After 1 hour, a second layer of Maestro liquid (if necessary) or a layer of Maestro impregnation can be applied to the previously sanded first layer (intercoat interval applies to normal working conditions).
transport and storage:	Store in a dry and well-ventilated place out of direct sunlight at a temperature of +5 to +25 °C.
shelf life:	In unopened packaging 24 months from the date of production.
certificates:	For each production batch, the relevant documentation is submitted.
product/package disposal:	Empty the packaging completely. Dispose of in accordance with valid regulations to an authorized waste collector.
quality control:	Product quality characteristics are determined by internal production specifications, as well as European and Croatian standards. The product is under the constant supervision of factory quality control Chromos-Svjetlost d.o.o.
disclaimers:	Before using the product, please check its quality. In case of any major deviations from the declared properties of the product, stop the use and contact the manufacturer; otherwise any subsequent complaints will not be accepted. Technical data are the result of our technical and experimental knowledge, and are provided

Technical Data Sheet

MAESTRO PROFI PUTTYING LIQUID

fast-drying liquid for filling joints of parquet



with the intention of achieving optimal results in working with CHROMOS- SVJETLOST products. The data does not contain a legal or secondary obligation of the manufacturer nor does it release the user from the obligation to check the suitability of the product for particular purpose. Due to the use of natural raw materials in our products, minor deviations from certain values are possible for individual deliveries. Contact our Technical service before use on substrates not listed in the accompanying documentation. The manufacturer reserves the right to make any subsequent changes to the Technical Data Sheet. Only the latest edition is valid. Updated Technical Data Sheets can be found on the website www.chromos-svjetlost.hr or can be requested from the manufacturer via the contact e-mail address below. Contact our Technical service for more detailed information. Be sure to read the safety labels on the product packaging before use. Safety Data Sheet is available on request.

October, 2021.

Quality and Environmental management systems certified in accordance with TÜV NORD Croatia;
Certificate No: 44 100 134668 / 44 104 134668

